

3/16 HIGH  
LETTERS

TO OPERATE PUMP AND BOOM

1. POSITION TRUCK AND SET PARKING BRAKE.
2. DEPRESS CLUTCH AND SHIFT TO 4TH GEAR HIGH.
3. TURN PTO ON.
4. RELEASE CLUTCH TO ENGAGE PUMPS.
5. SET THROTTLE AT 1400 RPM MAXIMUM.

TO RETURN TO DRIVING MODE

1. RETURN THROTTLE TO IDLE.
2. DEPRESS CLUTCH AND TURN PTO OFF.
3. SHIFT TO NEUTRAL AND RELEASE CLUTCH.

5

9

NOTES:

1. MATERIAL: .040 THK ALUMINUM, ADHESIVE BACKED
2. BLACK LETTERS ON BRUSHED ALUMINUM BACKGROUND.

				UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:			<b>REED</b>	CONCRETE PLACING EQUIPMENT			
				FRACT	DECIMAL	ANGLE		CHINO, CA 91710			
				1/32	.030	1/2°					
				DO NOT SCALE DRAWING			TITLE NAMEPLATE, PTO OPERATION				
				<b>C E</b>	BY	DATE	MATERIAL			PART NUMBER	REV
A	12/16/97	CHANGE RPM FROM 1250 TO 1400	JO	DRAWN	JIMO	7/21/97	THIS DRAWING IS THE PROPERTY OF REED MANUFACTURING AND IS LOANED WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED, OR DISPOSED OF, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED.			800059	A
LTR	DATE	ENGINEERING CHANGE NOTICE #	BY								
REVISIONS				APPVD						SHEET __ OF __	