PART NUMBER REV 800378

## 3/16 HIGH LETTERS

## TO OPERATE CONCRETE PUMP

- 1. POSITION TRUCK AND SET PARKING BRAKE.
- 2. DEPRESS CLUTCH FULLY AND TURN PTO KEY SWITCH TO PUMP POSITION.
- 3. SHIFT TO TRANSMISSION TO 6TH GEAR.
- 4. RELEASE CLUTCH TO ENGAGE PUMPS.
- 5. SET THROTTLE AT 1700 RPM MAXIMUM.

## TO RETURN TO DRIVING MODE

- 1. RETURN THROTTLE TO IDLE.
- 2. DEPRESS CLUTCH FULLY AND TURN PTO KEY SWITCH TO DRIVE POSITION.
- 3. SHIFT TO NEUTRAL AND RELEASE CLUTCH.

\_\_\_\_\_ 9 .

## NOTES:

- 1. MATERIAL: .040 THK ALUMINUM, ADHESIVE BACKED
- 2. BLACK LETTERS ON BRUSHED ALUMINUM BACKGROUND.

					S ARE IN :	SPECIFIED, INCHES AND ANGLE 1/2°	
				DO NOT SCALE DRAWING			NAMEPLATE, PTO OPERATION
				CE	BY	DATE	MATERIAL PART NUMBER REV
I TR	DATE	ENGINEERING CHANGE NOTICE #	BY	DRAWN	JIMO	1/6/98	THIS DRAWING IS THE PROPERTY OF REED MANUFACTURING AND IS LOANED WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED.
REVISIONS							OR DISPOSED OF, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY SHEETFURNISHED.