



## NOTES:

1. AFTER WELD DRIVE LINE MUST BE DINAMICLY BALANCED.

				DO NOT SCALE DRAWING			REED	CONCRETE PLACING EQUIPMENT	
				UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.				CHINO, CA 91710	
				TOLERANCES: .XX .030 .XXX .010 FRACTION 1/32 ANGLE 1/2°				TITLE DRIVE SHAFT FRONT, 37m	
				BREAK ALL SHARP EDGES .010 MAX. x 45°					
				ALL MACHINED SURFACES UNLESS OTHERWISE SPECIFIED			MATERIAL	PART NUMBER	REV
							THIS DRAWING IS THE PROPERTY OF REED MANUFACTURING AND IS LOANED WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED, OR DISPOSED OF, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED.		803147
REV	DATE	DESCRIPTION OF CHANGE	BY	DRAWN	SK	12/29/05			
REVISIONS				APPVD			SHEET 1 OF 1		