



NOTES:

1. AFTER WELD DRIVE LINE MUST BE DINAMICLY BALANCED.

				DO NOT SCALE DRAWING			REED		CONCRETE PLACING EQUIPMENT		
				UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.					CHINO, CA 91710		
				TOLERANCES: .XX .030 .XXX .010 FRACTION 1/32 ANGLE 1/2°			TITLE DRIVE SHAFT REAR, 37m				
				BREAK ALL SHARP EDGES .010 MAX. x 45°			MATERIAL		PART NUMBER 803148		REV
				ALL MACHINED SURFACES UNLESS OTHERWISE SPECIFIED							
REV	DATE	DESCRIPTION OF CHANGE	BY	DRAWN	SK	12/29/05	THIS DRAWING IS THE PROPERTY OF REED MANUFACTURING AND IS LOANED WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED, OR DISPOSED OF, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED.		SHEET 1 OF 1		
REVISIONS			APPVD								