



NOTES:

1. AFTER WELD DRIVE LINE MUST BE DINAMICLY BALANCED.

				DO NOT SCALE DRAWING			REED	CONCRETE PLACING EQUIPMENT		
				UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.				CHINO, CA 91710		
				TOLERANCES:				TITLE DRIVE SHAFT FRONT, 42m		
				.XX .030						
				.XXX .010						
				FRACTION 1/32			MATERIAL		PART NUMBER	REV
				ANGLE 1/2°						
				BREAK ALL SHARP EDGES .010 MAX. x 45			THIS DRAWING IS THE PROPERTY OF REED MANUFACTURING AND IS LOANED WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED, OR DISPOSED OF, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED.			
				ALL MACHINED SURFACES UNLESS OTHERWISE SPECIFIED						
REV	DATE	DESCRIPTION OF CHANGE	BY	DRAWN	SK	12/29/05	803149			
REVISIONS				APPVD			SHEET 1 OF 1			