



# NOTES:

1. AFTER WELD DRIVE LINE MUST BE DINAMICLY BALANCED.

				DO NOT SCALE DRAWING			<b>REED</b>	CONCRETE PLACING EQUIPMENT		
				UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.				CHINO, CA 91710		
				TOLERANCES: .XX .030 .XXX .010 FRACTION 1/32 ANGLE 1/2°				TITLE DRIVE SHAFT REAR, 37m WITH 309LR TRANS.		
				BREAK ALL SHARP EDGES .010 MAX. x 45°						
				ALL MACHINED SURFACES UNLESS OTHERWISE SPECIFIED						
REV	DATE	DESCRIPTION OF CHANGE	BY	DRAWN	SK	12/29/05	MATERIAL		PART NUMBER	REV
REVISIONS							THIS DRAWING IS THE PROPERTY OF REED MANUFACTURING AND IS LOANED WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT SHALL NOT BE REPRODUCED, COPIED, LOANED, OR DISPOSED OF, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED.		803259	
				APPVD					SHEET 1 OF 1	